

Specifications



SMART kapp™ 42" capture board (kapp42)

Overview


The SMART kapp™ 42" capture board enables you to collaborate with others in a simple but powerful way. Write and draw on the capture board like you would a regular dry erase board. You can then connect a Bluetooth®-enabled mobile device to the capture board by scanning a Quick Response (QR) code or by tapping the Near Field Communication (NFC) target. When you first connect your mobile device, you're directed to the Apple App Store or Google Play™ to download the SMART kapp app. After you download and install the app, you can use it to connect to your capture board and share content with others.

See smartkapp.com for more information on this product.



Dimensions and weights¹

Dimensions



Weight (approximate)

35 lb. (16 kg)

Shipping dimensions (approximate)

48" × 26" × 8"

(122 cm × 66 cm × 20.3 cm)

Shipping weight (approximate)

43 lb. (19.5 kg)

 $^{^{1}}$ All dimensions \pm 1/8" (0.3 cm). All weights \pm 2 lb. (0.9 kg).

SMART KAPP 42" CAPTURE BOARD (KAPP42)

Parts and features

Included parts SMART kapp 42" capture board

Dry-erase marker (×3)

Eraser

Bracket and hardware for mounting the capture board to a wall

Digital capture technology

DViT® (Digital Vision Touch) technology

Wireless technology

Bluetooth 2.1 + EDR²

Capture options

Establish a Bluetooth wireless connection with a supported mobile device (see below) by doing one of the following:

• Scan the capture board's unique QR code

• Tap the capture board's NFC target (Android™ devices only)

Connect a USB drive

USB drive support

USB 2.0 Type-A receptacle

Support for FAT-formatted USB drives only

Mobile device support

Apple devices iOS 7 or later operating system software

50 MB storage iPhone 4S or later

Third generation iPad or later First generation iPad mini or later

Android devices

Android 4.1 (Jelly Bean) or later operating system

50 MB of storage (internal or SD card)

Devices meeting the following specifications:

• 1024 MB of RAM

• 720p or better screen resolution

Bluetooth 2.1 + EDR

• NFC reader (recommended)

• 3 megapixel or better rear-facing camera (recommended)

Mounting

Options Included mounting bracket

Standard VESA® 400 mm \times 400 mm mounting bracket

Recommended height

69" (175.3 cm) from the floor to the middle of the included mounting bracket

 $^{^{2}}$ Compatible with Bluetooth 3.0 and dual-mode Bluetooth 4.0

Power

Power specifications 5V, 3A

Power cable 9' 10" (3 m) power cable

Storage and operating requirements

Storage

Temperature -40-140°F (-40-60°C)

Humidity 5–95% relative humidity, non-condensing

Operating

Temperature 41–95°F (5–35°C)

Humidity 10–80% relative humidity, non-condensing

Certification and compliance

Regulatory certification CE, ETL, C-Tick, FCC

Environmental compliance

European Union REACH, RoHS, WEEE and Packaging

U.S. Packaging and Conflict Minerals

Purchasing information

Order numbers

1024494 SMART kapp 42" capture board (kapp42)

Warranty One-year limited equipment warranty

Replacement parts Replacement pens and erasers can be purchased from the Store for SMART Parts

(see smarttech.com/Support/PartsStore)

smarttech.com/support smarttech.com/contactsupport

© 2014 SMART Technologies ULC. All rights reserved. SMART kapp, DVIT, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. Apple, iPhone and iPad are trademarks of Apple Inc., registered in the U.S. and other countries. Android and Google Play are trademarks of Google Inc. The Bluetooth word mark is owned by the Bluetooth SIG, Inc. and any use of such marks by SMART Technologies ULC is under license. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof covered by one or more of the following U.S. patents. www.smarttech.com/patents. Contents are subject to change without notice. 05/2014.